



Full Size End View
(1301 carrier shown)



No. 1300 Channel

1' - 4 oz.
13 gauge extruded aluminum, mill-finish. Obtainable in unspliced lengths up to 20'. Curved on the job or at the factory (optional) to a 2' minimum radius (layout dependent). Flange above carrier prevents tilting or climbing of carrier. Approximately: 5/8" wide x 1-11/16" high.



No. 1301 Carrier

4 - 3 oz.
Carrier spacing: 12". Constructed of plated steel wire supported from 2 solid nylon wheels. Plated swivel for free, effortless curtain movement. Carrier width: Approximately 1".



No. 1337 Nylon Ball-Bearing Single Carrier

1 - 1-1/2 oz.
Carrier spacing: 12". Constructed of plated steel wire supported from 2 nylon-tired ball-bearing wheels. Plated swivel for free, effortless curtain movement. Carrier width: Approximately 1".



No. 1301-A Single Carrier

1 - 2 oz.
Carrier spacing: 12". Block constructed of plated steel supported from 2 solid nylon wheels. Plated swivel for free, effortless curtain movement. Block provides "bumper-to-bumper" action. Carrier width: Approximately 1-1/8".



No. 1337-A Nylon Ball-Bearing Single Carrier

1 - 3 oz.
Carrier spacing: 12". Steel block supported from 2 nylon-tired ball-bearing wheels. Plated swivel for free, effortless curtain movement. Block provides "bumper-to-bumper" action. Carrier width: Approximately 1-1/8".