



SPECIFICATIONS:

RIG-I-FLEX® Model 141 [241] Curtain Tracks [Straight Track System]

Curtain tracks (Model 1400(BL)) shall be of 11 gauge extruded aluminum I-Beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4201(BL)**) shall be spaced on 12" centers and shall be of steel construction to include two nylon-tired ball-bearing wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Live-end (**Model 1403-B(BL)**) and Dead-end (**Model 1404(BL)**) pulley blocks shall be equipped with sleeve-bearing wheels adequately guarded. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. The manufacturer shall furnish two end stops (**Model 4209(BL)**) for placement at track ends and a tension floor pulley (**Model 2865(BL)**) for increasing cord tension. Track shall be rigidly supported from ceiling clamps (**Model 1423(BL)**) or hanging clamps (**Model 4208(BL)**). Stretch-resistant operating cord (Model 1728 for hand operating tracks and Model 3529 for machine operated tracks) shall have synthetic or wire center and shall be of 1/4" or 3/16" diameter. 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support all areas of all suspended curved tracks.

Model 141(241) as manufactured by Automatic Devices Company of Allentown, PA.

RIG-I-FLEX® Model 141-R [241-R] Curtain Tracks [Straight Track System]

Curtain tracks (Model 1400(BL)) shall be of 11 gauge extruded aluminum I-Beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4237(BL)**) shall be spaced on 12" centers and shall be of steel construction to include two solid nylon wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Live-end (**Model 1403-B(BL)**) and Dead-end (**Model 1404**) pulley blocks shall be equipped with sleeve-bearing wheels adequately guarded. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. The manufacturer shall furnish two end stops (**Model 4209(BL)**) for placement at track ends and a tension floor pulley (**Model 2865(BL)**) for increasing cord tension. Track shall be rigidly supported from ceiling clamps (**Model 1423(BL)**) or hanging clamps (**Model 4208(BL)**). Stretch-resistant operating cord (Model 1728 for hand operating tracks and Model 3529 for machine operated tracks) shall have synthetic or wire center and shall be of 1/4" or 3/16" diameter. 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support all areas of all suspended curved tracks.

Model 141-R(241-R) as manufactured by Automatic Devices Company of Allentown, PA.

RIG-I-FLEX® Model 142 [242] Curtain Tracks [Walk-Along Track System]

Curtain tracks (Model 1400(BL)) shall be of 11 gauge extruded aluminum I-Beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4201(BL)**) shall be spaced on 12" centers and shall be of steel construction to include two nylon-tired ball-bearing wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. Track shall be rigidly supported from ceiling clamps (**Model 1423(BL)**) or hanging clamps (**Model 4208(BL)**). Curves shall be formed on-the-job or at the factory. This model track system is for walk-along operation only and does not include pulleys or other operating hardware. 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support both straight and curved areas of all suspended curved tracks.

Model 142(242) as manufactured by Automatic Devices Company of Allentown, PA.

RIG-I-FLEX® Model 142-R [242-R] Curtain Tracks [Walk-Along Track System]

Curtain tracks (Model 1400(BL)) shall be of 11 gauge extruded aluminum I-Beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4237(BL)**) shall be spaced on 12" centers and shall be of steel construction to include two solid nylon wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. Track shall be rigidly supported from ceiling clamps (**Model 1423(BL)**) or hanging clamps (**Model 4208(BL)**). Curves shall be formed on-the-job or at the factory. This model track system is for walk-along operation only and does not include pulleys or other operating hardware. 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support both straight and curved areas of all suspended curved tracks. Model 142-R(242-R) as manufactured by Automatic Devices Company of Allentown, PA.