



No. 1600 Channel

1' - 7 oz.

16 gauge extruded aluminum, anodized finish. Obtainable in unspliced lengths up to 20'.

Approximately: 2-1/8" wide x 7/8" high.




No. 1131 Single Carrier

2 - 1 oz.

Carrier spacing: 6". Block, provides "bumper-to-bumper" action, and is supported from 2 polyethylene wheels. Plated swivel for free, effortless and quiet curtain movement.

Carrier width: Approximately 1-3/16".



No. 1602 Master Carrier [Default carrier]

1 - 2 oz.

Block constructed of plated steel supported from 4 polyethylene wheels. Provides **unlimited center overlap** with one curtain riding in front channel of track and one curtain riding in back channel of track.

Carrier length: Approximately 3-1/4".



No. 1132 Master Carrier

1 - 4 oz.

Similar to No. 1602 except equipped with 4" extension arm. Used on bi-parting track with fixed overlap. Also used on pinch-pleat installations in which all carriers are placed in the front channel. Provides 8" overlap. 4" in front of 4".

Carrier length: Approximately 7-3/8".



No. 1602-R Master Carrier

1 - 2 oz.

Block constructed of nylon and steel supported from 4 polyethylene wheels. Placed in rear channel to turn off limit switch on drapery machine when draperies reach fully closed position. Used with all motorized 160 systems.

Carrier length: Approximately 4-1/2".



No. 1131-B Single Carrier

2 - 1 oz.

Carrier spacing: 6". Block, provides "bumper-to-bumper" action, and is supported from 2 nylon-tired ball-bearing wheels.

Carrier width: Approximately 1-3/16".



No. 1132-B Master Carrier

1 - 4 oz.

Similar to No. 1132 except equipped with 4 nylon-tired ball-bearing wheels. Also used on pinch-pleat installations in which all carriers are placed in the front channel. Provides 8" overlap. 4" in front of 4".

Carrier length: Approximately 7-3/8".



No. 1624 Splicing Clamp

1 - 4 oz.

Steel clamp for joining track sections assuring proper track alignment.

Approximately: 6" long.



No. 1603 Live End Pulley

1 - 8 oz.

Used with **hand-operated** Model 160 track systems. Guides the operating cords down to a floor pulley located below.

Approximately: 2" long x 2" high x 2" wide.