




### No. 3526-AS Idler Bracket

1 – 6 oz.

Equipped with 1" steel ball-bearing wheel, used to guide cord around the outside of the curve (used on Dead-End half of the track system).

NOTE: For use with suspended type track systems only.



### No. 3561 Center Stop

1 - 8 oz.

End stop and idler combination for use only with 350 series tracks. Used at overlap on both track ends.



### No. 3516 Cord Retainer

1 - 2-1/2 oz.

Plated steel body with locking screw. Installed on upper portion of No. 3500 channel on side opposite master carrier. Retains cord in runway. For special applications only.



### No. 3525 Cord Connector

1 - 1 oz.

Used to splice cords adjacent to master carrier. Nylon coated. For use with hand-operated or motorized tracks.



### No. 3556 Track Straightening Tool

1 - 1 lb. 2 oz.

Extra accessory for smoothing out depressed areas of track walls.



### No. 3529 Cable

100' - 2 lbs. 7 oz.

Wire center with woven polyester cover. For machine-operated tracks. Partially concealed in track runways. 3/16" (No. 6)



### No. 2814 [BL] Pipe Clamp

1 pr. - 13 oz.

For 1-1/4" I.D. Schedule 40 pipe



### No. 2815 [BL] Pipe Clamp

1 pr. - 16 oz.

For 1-1/2" I.D. Schedule 40 pipe



### No. 2816 [BL] Pipe Clamp

1 pr. - 18 oz.

For 2" I.D. Schedule 40 pipe