



500



No. 5023A Ceiling Clamp for Walk-Along Systems

1 - 8 oz.
Used to ceiling mount Model 502 walk-along track systems. Allows track to be mounted directly to an overhead structure. Can ONLY be used with walk-along systems. Painted steel construction. Approximately: 3-5/8"L x 1-1/2"W



No. 5008-A(BL) Hanging Clamp

1 pr. - 4.5 oz.
Used with Model 502 suspended walk-along systems only.
Recommended spacing: 5' with additional units at curves and in stacking areas. Constructed of plated steel. Pipe batten recommended for track suspension. Approximately: 1-1/2"W x 2"L x 2"H



No. 5024(BL) Splicing Clamp

1 pr. - 1 lb. 3 oz.
Splicing bars for joining track sections assuring proper alignment of track. Approximately: 6" long x 3/8 wide x 7/8" high.



No. 5009 End Stop

1 - 1.5 oz.
Prevents carriers from moving beyond selected position in track. Located at center overlap and end of tracks.



No. 5007(BL) Lap Clamp

2 - 2 lbs. 13 oz.
For attaching double-sectioned track at center overlap. Assures proper spacing of tracks. Used with suspended bi-parting tracks only. Sold individually.



No. 5058 Cable Guide

1 - 1 lb. 2 oz.
Consists of nylon ball-bearing rollers for guiding cable along track channel. Drawing of track layout required when ordering to assure proper roller placement. Available in 3 layouts color coded white, red, yellow.



No. 2866(BL) Adjustable Floor Pulley

1 - 5-1/2 lbs.
For manual operation. Equipped with 1 - 5" diameter glass-filled nylon ball-bearing wheel. Locks in place via threaded axle. Adjustment - 7". Approximately: 3" long x 5-1/2" wide x 13" high.



No. 2828 Cord

100' - 5 lbs. 7 oz.
For manual operation only. 3/8" diameter (No. 12)



No. 5029 Cable

100' - 3 lbs. 10 oz.
Wire center with extruded nylon cover. For machine operated 500 Series tracks only. 3/16" diameter (No. 6)