



		140 RIG-I-FLEX® CWANA code					
		CORD OPERATED/MOTORIZED				WALK-ALONG	
Parts Included		140 (240)	140-R (240-R)	141 (241)	141-R (241-R)	142 (242)	142-R (242-R)
STRAIGHT				√	√	√	√
CURVED		√	√				
Single Carriers	4201 (BL)	√		√		√	
	4237 (BL)		√		√		√
Master Carriers	1438 (BL)			√	√		
	1402 (BL)	√	√				
	4252 (BL)					√	
	4253						√
Pulleys	1403	√	√				
	1403-B			√	√		
	1404	√	√	√	√		
	2865 (BL)	√	√	√	√		
Spindles & Idlers	1458 (BL)	√	√				
	1459 (BL)	√	√				
	1460 (BL)	√	√				
Cord	1728	√	√	√	√		

BL = Black Finish
2XX Series Track
Systems have a black finish.

140

SPECIFICATIONS:

RIG-I-FLEX® Model 140 [240] Curtain Tracks

Curtain tracks Model 1400(1400BL) shall be of 11 gauge extruded aluminum I-Beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4201(BL)**) shall be spaced on 12" centers and shall be of steel construction to include two nylon-tired ball-bearing wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Live-end (**Model 1403**) and Dead-end (**Model 1404**) pulley blocks shall be equipped with sleeve-bearing wheels adequately guarded. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. The manufacturer shall furnish two end stops (**Model 4209(BL)**) for placement at track ends and a tension floor pulley (**Model 2865(BL)**) for increasing cord tension. Track shall be rigidly supported from ceiling clamps (**Model 1423(BL)**) or hanging clamps (**Model 4208(BL)**). Stretch-resistant operating cord (Model 1728 for hand operating tracks and Model 3529 for machine operated tracks) shall have synthetic or wire center and shall be of 1/4" or 3/16" diameter. Curves require ball-bearing spindles (**Models 1458(BL) & 1459(BL)**) and ball-bearing idlers (**Model 1460(BL)**). 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support both straight and curved areas of all suspended curved tracks.

Model 140(240) as manufactured by Automatic Devices Company of Allentown, PA.

RIG-I-FLEX® Model 140-R [240-R] Curtain Tracks

Curtain tracks Model 1400(1400BL) shall be of 11 gauge extruded aluminum I-Beam construction consisting of a center rib and top, intermediate and bottom flanges. Each curtain carrier (**Model 4237(BL)**) shall be spaced on 12" centers and shall be of steel construction to include two solid nylon wheels rolling on two separate parallel treads. Each curtain carrier shall consist of a free-moving plated swivel to accommodate curtain snap hook. Live-end (**Model 1403**) and Dead-end (**Model 1404**) pulley blocks shall be equipped with sleeve-bearing wheels adequately guarded. Nylon snap-on spacers shall be attached to wheel supports of curtain carriers. The manufacturer shall furnish two end stops (**Model 4209(BL)**) for placement at track ends and a tension floor pulley (**Model 2865(BL)**) for increasing cord tension. Track shall be rigidly supported from ceiling clamps (**Model 1423(BL)**) or hanging clamps (**Model 4208(BL)**). Stretch-resistant operating cord (Model 1728 for hand operating tracks and Model 3529 for machine operated tracks) shall have synthetic or wire center and shall be of 1/4" or 3/16" diameter. Curves require ball-bearing spindles (**Models 1458(BL) & 1459(BL)**) and ball-bearing idlers (**Model 1460(BL)**). 1-1/4" I.D. stiffening pipe or the equivalent shall be used to support both straight and curved areas of all suspended curved tracks.

Model 140-R(240-R) as manufactured by Automatic Devices Company of Allentown, PA.